TANK-POWER END MILLS

UNCOATED **E9A31** SERIES
TiAlN COATED **GAA31** SERIES

HSS-PM, 4 FLUTE LONG LENGTH

HSS-PM, 4 SCHNEIDEN LANG
FRAISES HSS-PM, 4 DENTS, SÉRIE LONGUE
4 TAGLIENTI, SERIE LUNGA, HSS-PM

- Designed to machine carbon steels, alloyed steels, stainless steels.
- Recommended for pocketing, cam milling, die sinking and slotting.
- Designed for high speed cutting of difficult-to-cut materials.
- YG-1's new developed TANK-POWER Coating suitable for high speed cutting.

- Geeignet zum Fräsen von Stahl, legiertem Stahl und rostfreier Stahl.
- Empfohlen für Taschenfräsen, Nockenfräsen, Gussformen und Nutenfräsen.
- Geeignet für Hochgeschwindigkeitsfräsen von schwer zu zerspanenden Materialien.
- Neuentwickelte Beschichtung für Hochgeschwindigkeitsfräsen.





HSS PM | DIN 844 | 4 | 30° | DIN 1835B | UNCOATED | TiAlN

p.C696~C697

Recommended ToolHolder	Flat Shank	Plain Shank
	END MILL HOLDER	POWER MILLING CHUCK
	-	ER COLLET CHUCK SK SLIM CHUCK

Unit : mm

EDP No.		Mill Diameter	Shank Diameter	Length of Cut	Overall Length
UNCOATED	TiAlN				
E9A31020	GAA31020	2.0	6	10	54
E9A31030	GAA31030	3.0	6	12	56
E9A31040	GAA31040	4.0	6	19	63
E9A31050	GAA31050	5.0	6	24	68
E9A31060	GAA31060	6.0	6	24	68
E9A31070	GAA31070	7.0	10	30	80
E9A31080	GAA31080	8.0	10	38	88
E9A31090	GAA31090	9.0	10	38	88
E9A31100	GAA31100	10.0	10	45	95
E9A31120	GAA31120	12.0	12	53	110
E9A31140	GAA31140	14.0	12	53	110
E9A31160	GAA31160	16.0	16	63	123
E9A31180	GAA31180	18.0	16	63	123
E9A31200	GAA31200	20.0	20	75	141
E9A31220	GAA31220	22.0	20	75	141
E9A31250	GAA31250	25.0	25	90	166

Mill Dia. Tolerance (mm)	Shank Dia. Tolerance
0 ~ −0.03	h6

◎ : Excellent ○ : Good

ISO	P											M			K					
Material Description	Non-alloy steel					Low alloy steel				High alloyed steel, and tool steel		Stainless steel			Grey cast iron		Nodular cast iron		Malleable cast iron	
VDI 3323	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
HRc		13	25	28	32	10	29	32	38	15	35	15	23	10	10	26	3	25		21
HB	125	190	250	270	300	180	275	300	350	200	325	200	240	180	180	260	160	250	130	230
Recommend	◎	◎	◎	◎	◎	◎	◎	◎	○	◎	○	◎	◎	◎	◎	◎	◎	◎	◎	◎

ISO	N										S							H			
Material Description	Aluminum-wrought alloy		Aluminum-cast, alloyed			Copper and Copper Alloys (Bronze / Brass)			Non Metallic Materials		Heat Resistant Super Alloys					Titanium Alloys		Hardened steel		Chilled Cast Iron	Hardened Cast Iron
VDI 3323	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41
HRc											15	30	25	38	34			55	60	42	55
HB	60	100	75	90	130	110	90	100			200	280	250	350	320	400 Rm	1050 Rm	550	630	400	550
Recommend						○	○	○													