YG TAP INOX

TBE15 SERIES

M ISO metric coarse threads DIN 13


Metrisches ISO-Gewinde DIN 13
ISO MÉTRIQUE DIN13
ISO Metrico passo grosso DIN 13

Machine taps
Maschinengewindebohrer

- With recessed threads for machine tapping of deep blind holes.
- Suitable for tapping blind holes due to special flute geometry and excellent chip evacuation.

- Mit abgesetztem Gewinde zum Schneiden von tiefen Sacklochgewinden.
- Geeignet zum Gewinden von Sacklöchern dank besonderer Nutengeometrie und ausgezeichneter Spanabfuhr.


DIN 371





DIN 376




Hole type
2.5×D









Material groups: VA NW | HSS-E | DIN 371/376 | 4H | 60° | C | R40 | Vap

p.B193

Recommended ToolHolder: Plain Shank — TAPPING ER CHUCK, TAPPING CHUCK, ONE STEP TAPPING CHUCK

Unit : mm

SIZE	Pitch	EDP No.	Thread Length	Overall Length	Neck Length	Shank Diameter	Square Size	Square Length	No. of Flute	Tapping Drill Diameter
ØD1	P	Vap	L1	L2	L3	ØD2	K	Kl	Z	Ød1
M2	× 0.4	TBE15136	8	45	13	2.8	2.1	5	3	1.6
M2.2	× 0.45	TBE15156	8	45	13	2.8	2.1	5	3	1.75
*M2.3	× 0.4	TBE15196	8	45	13	2.8	2.1	5	3	1.9
M2.5	× 0.45	TBE15176	9	50	15	2.8	2.1	5	3	2.05
*M2.6	× 0.45	TBE15496	9	50	15	2.8	2.1	5	3	2.1
M3	× 0.5	TBE15206	6	56	18	3.5	2.7	6	3	2.5
M3.5	× 0.6	TBE15226	7	56	20	4	3	6	3	2.9
M4	× 0.7	TBE15246	7	63	21	4.5	3.4	6	3	3.3
M4.5	× 0.75	TBE15266	8	70	25	6	4.9	8	3	3.7
M5	× 0.8	TBE15286	8	70	25	6	4.9	8	3	4.2
M6	× 1.0	TBE15316	10	80	30	6	4.9	8	3	5
M7	× 1.0	TBE15346	10	80	30	7	5.5	8	3	6
M8	× 1.25	TBE15366	13	90	35	8	6.2	9	3	6.8
M9	× 1.25	TBE15396	13	90	35	9	7	10	3	7.8
M10	× 1.5	TBE15426	15	100	39	10	8	11	3	8.5
M11	× 1.5	TBE15466	17	100	40	8	6.2	9	3	9.5
M12	× 1.75	TBE15506	18	110	44	9	7	10	3	10.2
M14	× 2.0	TBE15546	20	110	44	11	9	12	3	12
M16	× 2.0	TBE15606	20	110	44	12	9	12	3	14
M18	× 2.5	TBE15656	25	125	50	14	11	14	4	15.5
M20	× 2.5	TBE15706	25	140	54	16	12	15	4	17.5
M22	× 2.5	TBE15746	25	140	54	18	14.5	17	4	19.5
M24	× 3.0	TBE15786	30	160	60	18	14.5	17	4	21
M27	× 3.0	TBE15866	30	160	60	20	16	19	4	24
M30	× 3.5	TBE15946	35	180	70	22	18	21	4	26.5

- DIN 371(M2~M10) and DIN 376(M11~M30)
- * DIN profile not ISO

◎ : Excellent ○ : Good

ISO	P											M			K					
Material Description	Non-alloy steel					Low alloy steel				High alloyed steel, and tool steel		Stainless steel			Grey cast iron		Nodular cast iron		Malleable cast iron	
VDI 3323	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
HRc		13	25	28	32	10	29	32	38	15	35	15	23	10	10	26	3	25		21
HB	125	190	250	270	300	180	275	300	350	200	325	200	240	180	180	260	160	250	130	230
Recommended	◎	◎	○	○		○						◎	◎	◎						

ISO	N										S					H					
Material Description	Aluminum-wrought alloy		Aluminum-cast, alloyed			Copper and Copper Alloys (Bronze / Brass)			Non Metallic Materials		Heat Resistant Super Alloys					Titanium Alloys		Hardened steel		Chilled Cast Iron	Hardened Cast Iron
VDI 3323	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41
HRc											15	30	25	38	34			55	60	42	55
HB	60	100	75	90	130	110	90	100			200	280	250	350	320	400Rm	1050Rm	550	630	400	550
Recommended											○					○					

phone:+82-32-526-0909, www.yg1.solutions, E-mail:yg1@yg1.solutions
YG-1 CO., LTD.